

Gooseneck Coupler Head

Can be mounted on the trailer as a standard gooseneck coupler or in the truck bed. Removable steel pin secures hitch ball in the cast housing. Meets rated capacity only when used with the pin supplied.



K1

Part No.	Ref. No.	Ball	Description	Capacity
K1	291300	2 5/16"	Coupler Head with 1/2" Lock Pin	30,000 lbs
K2	291900	3"	Coupler Head with 3/4" Lock Pin	40,000 lbs
12SL	293920		Replacement Lock Pin for K1 Coupler	
34SL	293925		Replacement Lock Pin for K2 Coupler	

Gooseneck Couplers

JACKS,
COUPLERS &
WINCHES



GG2516ADJ



ST2516NP

A leader in the industry! Superior features a cast cone shaped bottom plate and a heavy-duty cast handle. Available in round or square tube design, both adjustable and nonadjustable.

Part No.	Ref. No.	Ball	Tube O.D.	Overall Height	Extended Height	Capacity
ST2516NP	291200	2 5/16"	Coupler Head Only, No Pipe			20,000 lbs
ST251632	292200	2 5/16"	4 1/2" Round	32"	Non-adjustable	20,000 lbs
SAC2516	293000	2 5/16"	4 1/2" Round	28"	38"	24,000 lbs
SAC2516-LP	293025	2 5/16"	4 1/2" Round	30"	42"	24,000 lbs
GG2516ADJ	293100	2 5/16"	4 1/2" Round	30"	38"	30,000 lbs
SQ2516ADJ	293200	2 5/16"	4 1/2" Square	32"	40"	20,000 lbs
SAC2516-IP	293800	2 5/16"	4" Round		Replacement Inner Assembly for #SAC 2516	24,000 lbs
SAC-BOLT	293900				Replacement 3/4" -10 x 3" Set Screw for #SAC2516	
SAC-NUT	293910				Replacement 3/4" Nut for #SAC2516	



HBQ2516TW



HBQ2516ADJ



BULLDOG® gooseneck couplers have a fabricated cone shaped bottom plate. The #HBQ2516ADJ features a user-friendly cam lock height adjustment design allowing hands free modifications.

Part No.	Ref. No.	Ball	Tube O.D.	Overall Height	Extended Height	Capacity
HB2516NP	291250	2 5/16"	Coupler Only, No Pipe			20,000 lbs
HBA2516	293050	2 5/16"	4 1/2" Round	29 1/2"	40 1/2"	20,000 lbs
HBQ2516ADJ	293150	2 5/16"	4 1/2" Square	31 3/4"	42 1/2"	20,000 lbs
HBQ2516TW	293158	2 5/16"	4 1/2" Square	32"	39"	30,000 lbs

Gooseneck Couplers (continued)

T.E.M.'s "AutoLock" design works on the same principle as a 5th wheel. The jaws of the coupler open and unhook from the hitch ball without having to raise or lower the coupler. Their standard gooseneck couplers (SH and BH series) feature a spring-action automatic closing bottom plate and deep cast cone-shaped bottom plate for easier line-up of coupler and ball. The BH series offers greater capacity utilizing a forged steel one-piece top plate.



AutoLock						
Part No.	Ref. No.	Ball	Tube O.D.	Overall Height	Extended Height	Capacity
SM2516NP	291400	2 5/16"	Coupler Only, No Pipe			24,000 lbs
SM251628	292400	2 5/16"	4" Round	28"	Non-adjustable	24,000 lbs
LL2516ST	293400	2 5/16"	4" Square	28"	38"	24,000 lbs

Standard						
Part No.	Ref. No.	Ball	Tube O.D.	Overall Height	Extended Height	Capacity
SH2516SRD	293060	2 5/16"	4 1/2" Round	28"	38"	25,000 lbs
BH2516SRD	293110	2 5/16"	4 1/2" Round	28"	38"	30,000 lbs



JACKS,
COUPLERS &
WINCHES



The Fulton® adjustable gooseneck coupler provides 14.5" of adjustability and four set screws for added strength. The prime finish eliminates preparation time for painting. Customize your fabrication by using the coupler head only.

Part No.	Ref. No.	Ball	Tube O.D.	Overall	Extended	Capacity
				Height	Height	
GNT24	292501	2 5/16"	4.5"	24"	38.5"	24,000 lbs
GN24	291500	2 5/16"	Coupler head only			24,000 lbs



Without the *Glider Coupler™*, the bumps and jolts of the road put extreme stress on your truck's drive train, suspension, body and tires - the results of which can be costly repairs, shorter vehicle life and a very uncomfortable ride.

The Glider Coupler™

- Absorbs jerks and bounces through a gravity self-centering, parallel linkage system.
- Greatly reduces stress and fatigue at the hitch point.
- Helps prolong the life of your truck and trailer.
- Doesn't affect braking or steering.
- Makes for a smoother more pleasant ride.
- Rated at 24,000 lbs. GTW, 4,000 lbs. tongue wt.
- Fits into existing 4 1/2" OD outer pipe.

Part No.	Ref. No.	Ball	Description	Capacity
GC2516	293797	2 5/16"	Coupler, less outer pipe	24,000 lbs





King Pin Gooseneck Coupler

Most gooseneck trailers are designed to be towed on a gooseneck hitch ball located in the bed of the tow vehicle. However, this king pin and pipe assembly is designed for those wanting to tow a gooseneck trailer with a 5th wheel hitch. **The king pin is specially designed with zero bolster.** The 4" O.D. round tube will fit as an inner pipe on most standard gooseneck outer tubes. Always follow manufacturer's torque specs when tightening set screws.

Part No.	Ref. No.	Pipe	Description	Capacity
2085205	293799	22"	4" O.D. Round Tube, 22" Long, Less outer tube.	30,000 lbs

Flat Mount Couplers

A flat mount coupler is an excellent alternative to tow rings or pintle hooks. These standard ball couplers work with 2 5/16" hitch balls. Mounts to most trailer nose plates.

Part No.	Ref. No.	Ball	Finish	Capacity
75074	269350	2 5/16"	Painted	25,000 lbs
FMC251614	305817	2 5/16"	Painted	14,000 lbs



75074



FMC251614

Square Mount Draw Bars and Nose Plates



1250-15

Commonly used on equipment and over-the-road trailers, the flat back design of the following Draw Bars allows easy mounting on the nose plate. The bolt kits are approved for use with the respective draw bars/nose plates.

Square Mount Draw Bars						
Part No.	Ref. No.	Type	Eye Diameter	GTW lbs.	Bolt Pattern	
1250-15	308400	Holland	2 1/2"	40,000	4 Bolt, 6" Square	
R49A	308401	Wallace	2 1/2"	42,000	4 Bolt, 6" Square	
1385	308600	Holland	3"	60,000	4 Bolt, 6" Square	
R51A	308601	Wallace	3"	66,000	4 Bolt, 6" Square	



TNP71675

Nose Plates			
Part No.	Ref. No.	Description	For Use with:
TNP71675	308410	8 hole, 3/4" x 7" x 16"	R49A & 1250-15
TNP716100	308610	8 hole, 1" x 7" x 16"	R51A & 1385
BLT71675	308412	4 bolts, 4 nuts, 4 washers	TNP71675
BLT716100	308612	4 bolts, 4 nuts, 4 washers	TNP716100